Introduced by Committee on Transportation (Dutra (Chair), Chan, Chu, Liu, Longville, Nakano, Oropeza, Parra, Pavley, Salinas, and Simitian)

February 27, 2003

An act to amend Section 24403 of the Vehicle Code, relating to vehicles.

## LEGISLATIVE COUNSEL'S DIGEST

AB 1718, as introduced, Committee on Transportation. Vehicles: motorcycles: foglamps.

Existing law authorizes a motor vehicle to be equipped with not more than 2 foglamps that may be used with, but may not be used in substitution of, headlamps. Existing law requires foglamps are required to be mounted on the front at a height of not less than 12 inches nor more than 30 inches and so aimed that when the vehicle is not loaded none of the high-intensity portion of the light to the left of the center of the vehicle projects higher than a level of 4 inches below the level of the center of the lamp from which it comes, for a distance of 25 feet ahead of the vehicle.

This bill would authorize for motorcycles the mounting height for the foglamps to be not more than 40 inches.

Vote: majority. Appropriation: no. Fiscal committee: no. State-mandated local program: no.

AB 1718 — 2 —

The people of the State of California do enact as follows:

SECTION 1. Section 24403 of the Vehicle Code is amended to read:

- 24403. (a) Any A motor vehicle may be equipped with not to exceed more than two foglamps which that may be used with, but shall may not be used in substitution of, headlamps. Foglamps
- (b) On a motor vehicle other than a motorcycle, the foglamps authorized under this section shall be mounted on the front at a height of not less than 12 inches nor more than 30 inches and so aimed so that when the vehicle is not loaded none of the high-intensity portion of the light to the left of the center of the vehicle shall at a distance of 25 feet ahead project projects higher than a level of four inches below the level of the center of the lamp from which it comes, for a distance of 25 feet in front of the vehicle.
- (c) On a motorcycle, the foglamps authorized under this section shall be mounted on the front at a height of not less than 12 inches nor more than 40 inches and aimed so that when the vehicle is not loaded none of the high-intensity portion of the light to the left of the center of the vehicle projects higher than a level of four inches below the level of the center of the lamp from which it comes, for a distance of 25 feet in front of the vehicle.